ALUMINUM STRIP CEILINGS

C-Type (84 c /184c) (Plain / Perforated)

TECHNICAL DATA SHEET



Product Specifications Aluminum alloy 3005, 3105. comply with BS 476 PART 7-1987 ,ASTM B Material 209, ASTM D 2247, ASTM E 1477-98 and EN 1396. 0.5 other thickness **Thickness** Standard Colors Available in 110 different colors. pre-painted polyester coating (primer+polyster) thk=25 microns from **Finish** front & (polyester)5 microns from the back According to EN 1396. Class 0 as per british standard BS 476 PART 7-1987. Surface Flame Spread test Fire Rating (Raw Material) Class 0 as per british standard BS 476 PART 6 & 7 **Humidity resistance** up to 1000 HRS According to ASTM D 2247. (Raw Material) more than 0.8 According to ASTM E **Light Reflectance** 1477-98. (Raw Material) Available with perforation for acoustical **Acoustical Properties** usage(circular perforation 1.8mm) with acoustical black tissue from the backside. (84C) which provides a MODULE Width of Sizes (184C) which provides a MODULE Width of 200 mm.

System Contents (Components)

- 1. C-type Wide strip Aluminum panel.
- 2. C-carrier (4000mm length) Made of hot dipped galvanized steel THK = 0.55MM.
- 3. Border Angle / Wall Angle (4000mm length)
 Made of panel same material (Available in 2 types
 L-Angle & U -Angle shapes).

Features and Benefits:











High-quality properties of non-combustibility and mechanical stability.

Fire & moisture resistance, corrosive resistance & light reflection.









Easy to clean, durable, easy to install.

Available as perforated for acoustical usage.

Environmentally friendly and recyclable.

Applications

Wide range for usage/application area (bathrooms, kitchens, wet areas, halls, outdoor bottom covering, hospitals, shops, offices, airports, exhibition centers ...etc).





Supplier and Manufacturer: JAWDAH INDUSTRIAL COMPANY LTD. **Country of Origin:** Kingdom of Saudi Arabia

